

Click & Fix

Product Description

Soudafoam FR Click&Fix is a one-component, selfexpanding, ready to use polyurethane foam. It has been fitted with the unique patented Click&Fix adaptor system for maximum comfort in use. It contains propellants, which are completely harmless to the ozone layer. It has a fire rating of up to 360 minutes.

Features

- Efficient seal against smoke and gas
- Excellent adhesion on most substrates (exempt Teflon, PE and PP)
- Can be painted after full cure
- High bonding strength

Typical Applications

- Fire retardant installation of window and doorframes
- Fire- and smoke retardant sealing of connections between partition walls, ceilings and floors
- Filling of cavities



Soudafoam FR Click&Fix	
Base	Polyurethane
Consistency	Stable foam
Curing system	Moisture-cure
Skin formation - (20°C/65 % R.H.)	Ca 10 min.
Drying time - (20°C/65 % R.H.)	Tackfree after 25 min.
Curing rate - (20°C/65 % R.H.)	2h for a 30 mm bead
Yield	1000 ml yields 35-40 L cured foam when extruded in beads
Shrink	None
Postexpansion	None
Colour	Light red
Cellular structure	>70 % closed cells
Specific gravity	Ca. 25 kg/m ³ extruded, fully cured
Temperature resistance	-40°C to +90°C when cured

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. October 2014