

VHT013 Clear Double Coated Tape

Product Description

VHT013 Clear Double Coated Tape is a high performance double coated clear Polyester tape.

Characteristics

- High tack and shear strength
- Excellent low and elevated temperature performance
- Superior moisture resistance in high humidity



Typical Applications

The product is specified by Kingspan for use on their Topdek Insulated Single Ply Roofdeck system to ensure a flat side lap detail when using mechanical hot air welding equipment.

VHT013	
Support	Non-woven, 12 g/m ²
Interliner	Release paper, yellow, 90 g/m ²
Adhesive Weight	90 g/m ²
Total Thickness	0,10 mm
Temperature Resistance (According to the ATP test method AA-B-12-07)	from -40°C to +90°C
Adhesive Strength (According to AFERA 5001)	min. 21 N/25 mm Contact time: 1 hour

Adhesive

MF-adhesive is a modified polyacrylate and has good, all-round adhesive properties especially with reference to ageing and weathering properties. It has very good initial tack with very high peel adhesion to a wide variety of low surface energy substrates such as foams, PE, PP and EPDM. MF-adhesive is an ideal lamination adhesive for a wide variety of laminates.

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. October 2014