

Butyl Tape MLL10

Product Description

MLL10 is a grey-coloured, synthetic rubber based preformed strip sealant, laminated with a fixed foil backing. For information on available sizes, please visit our website.

Features

- Slit to order - many widths available
- Flexible and comfortable



Typical Applications

- Sealing membranes
- Flashing of canopies, doors, window frames and conservatories
- Over-sealing or repair of joints in gutters and downpipes
- Air sealing on liner panels in twin skin construction (side lap only)
- Vapour sealing on cold store panels

MLL10	
Thickness	0.6mm
Widths	From 40mm to 1000mm
Roll length	15m
Adhesion	Good adhesion to a wide range of substrates
Peel strength	4 N/cm ²
Movement	Good creep resistance
Service temperature	-30°C to +80°C
Application temperature	+5°C
UV resistance	Excellent
Chemical resistance	Good to mild acids and alkalis
Permeability to vapour (sealant component only)	2.5 g/m ² /24h
Shelf life	1 year

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. October 2014

Premier Sealant Systems Ltd

Mercia Way Foxhills Industrial Park Scunthorpe, DN15 8RE, England

Tel. 01724 864100 | Fax. 01724 860116 | Email. sales@premseal.co.uk | Website. www.premseal.co.uk