

Butyl Tape MLL10

Product Description

MLL10 is a grey-coloured, synthetic rubber based preformed strip sealant, laminated with a fixed foil backing. For information on available sizes, please visit our website.

Features

- Slit to order - many widths available
- Flexible and comfortable



Typical Applications

- Sealing membranes
- Flashing of canopies, doors, window frames and conservatories
- Over-sealing or repair of joints in gutters and downpipes
- Air sealing on liner panels in twin skin construction (side lap only)
- Vapour sealing on cold store panels

MLL10	
Thickness	0.6mm
Widths	From 40mm to 1000mm
Roll length	15m
Adhesion	Good adhesion to a wide range of substrates
Peel strength	4 N/cm ²
Movement	Good creep resistance
Service temperature	-30°C to +80°C
Application temperature	+5°C
UV resistance	Excellent
Chemical resistance	Good to mild acids and alkalis
Permeability to vapour (sealant component only)	2.5 g/m ² /24h
Shelf life	1 year

Please note: The above technical information is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish suitability of the product for the intended application. October 2014

Premier Sealant Systems Ltd

Mercia Way Foxhills Industrial Park Scunthorpe, DN15 8RE, England

Tel. 01724 864100 | Fax. 01724 860116 | Email. sales@premseal.co.uk | Website. www.premseal.co.uk

Premseal strip Butyl

Storage and Transportation Advice

STORAGE TEMPERATURE: between 5 °C and 25 °C Ambient

TRANSPORT TEMPERATURE: between 5 °C and 25 °C Ambient

LOADING/UNLOADING TEMPERATURE: Ambient

VISCOSITY (cSt): Not Applicable

STORAGE/TRANSPORT PRESSURE (kPa): Atmospheric

ELECTROSTATIC ACCUMULATION HAZARD? No, not from product, slight static charge may be developed from the removal of the release paper, if relevant use appropriate grounding procedures

USUAL SHIPPING CONTAINERS: This product can be transported by shipping container. Where possible avoid any excessive heat and prolonged exposure. Continuous exposure may impact on ease of application. Supplied in cardboard cartons.

MATERIALS AND COATINGS UNSUITABLE: None

STORAGE / HANDLING, GENERAL NOTES: Store in a cool, well-ventilated place away from incompatible materials. Do NOT remove release liner or store cartons of product near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Shelf life more than 24 months in ambient conditions.

Storage temperatures between 5 °C and 25 °C would be advisable however storage outside of these temperatures is possible hence the terms cool and ambient.

The key to keeping material fit for purpose is to keep it dry.

IF STORAGE AND TRANSPORTATION IS BELIEVED TO BE BEYOND THESE CONDITIONS PLEASE CONTACT US TO DISCUSS FURTHER



Premier Sealant Systems Ltd.

T 01724 864 100 | E sales@premseal.co.uk | www.premseal.co.uk

Mercia Way, Foxhills Industrial Park, Scunthorpe, DN15 8RE
Registered Office: 19 Titan Court, Luton, LU4 8LL | Registered in Cardiff No. 3000843